

# SNBC

Extraordinary  
Value!

# BTP-R880NP

Thermal Receipt Printer



Contains Everything Necessary – Including the Communications Cables – in the Carton

## The Best Value in its Class!

The BTP-R880NP thermal receipt printer is a second generation NP class printer produced by SNBC – a leading manufacturer of printers and thermal print heads. The BTP-R880NP is compatible with most popular POS software applications, many POS systems and fits a wide variety of mini-printer applications.

- Energy Star Certified – Superior Efficiency Reduces Energy Costs and Reduces Carbon Footprint
- Extraordinary Reliability Backed by 3 Year Bumper-to-Bumper Warranty
- Gray Scale and Two Color Print Capable
- 230mm per Second Print Speed
- Dual Interface Standard – USB Interface is on the Main Board
- Stores/Prints Coupon and Logo Images
- Prints Watermarks



# BTP-R880NP Thermal Receipt Printer



**Drop and Print Paper Loading.** Included Paper Width Selectors Allow 58mm Paper Rolls



**Liquid Guard Built Into the Cabinet Design**



**Built-In Wall Mount Capability and Optional Audio/Visual Print Messenger**



**Optional Spill Cover**

## Features

A low-cost high quality thermal receipt printer ideal for demanding environments.

- Serial, Parallel, USB, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Can use the Same Interface Boards as Other SNBC Printers
- Programmable Paper Saving Options
- Programmable Internal Alarm Volume
- Easy Firmware Upgrade by USB Memory Stick
- Auto-Cutter – Selectable Full or Partial Cut
- Drop and Print Paper Loading
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches – Intuitive Keypad Programming
- Supports Asian Character Sets with Standard Memory
- Includes Starter Paper Roll, Two Paper Width Selectors, Communications Cable, USB Cable, Power Adapter and Cord, Power Switch Cover, Reversed Label for Wall Mounting and CD-ROM with Drivers, Utilities and User's Manual

## Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Powered USB Cable
- Spill Cover
- Power Supply Cover

## Ports and Connectivity

**A** DC 24V Power-In

**B** Cash Drawer

**C** USB

**D** Choice of Serial (Shown), Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available

**E** Cable Management Clip

## Specifications

<b>Print Speed:</b>	230mm per Second / 63 Lines per Second
<b>Characters Per Line – Font A:</b>	42 (80mm) / 37 (58mm)
<b>Font B:</b>	56 (80mm) / 49 (58mm)
<b>Characters Size – Font A:</b>	12 x 24
<b>Font B:</b>	9 x 17
<b>Paper Roll Type – Width:</b>	82.5±0.5mm, 80.0±0.5mm, 76.0±0.5mm, 69.5±0.5mm, 57.5±0.5mm
<b>Maximum Diameter:</b>	83mm
<b>Paper Thickness:</b>	.06mm ~ 0.1mm
<b>Reliability – MTBF:</b>	360,000 Hours
<b>MCBF:</b>	60,000,000 Lines
<b>Printhead Life:</b>	≥ 150 KM
<b>Cutter Life:</b>	1,800,000 Cuts
<b>Character Set –Alphanumeric:</b>	95
<b>International:</b>	Traditional Chinese, Simplified Chinese, Japanese, Korean, and More (Optional)
<b>Graphic:</b>	128 x 56
<b>Bar Code – 1D:</b>	UPC-A / UPC-E / JAN8 (EAN8) / JAN13 (EAN13) / Code39 / Code93 / CODE128 / ITF / CODABAR
<b>2D:</b>	PDF417 / QR / MaxiCode / GS1 Databar
<b>Interpreter:</b>	ESC/POS™
<b>Interface:</b>	USB, Serial/USB, Parallel/USB, Ethernet/USB, WiFi/USB
<b>Driver:</b>	Windows® POSReady 2009 / Windows 7 32 & 64 bit / Server 2008 32 & 64 bit / Vista 32 & 64 bit / Server 2003 32 & 64 bit / XP Professional 32 & 64 bit / 2000 Server / 2000 Professional / Linux CUPS / MAC / OPOS
<b>Drawer Port:</b>	2 Port (+24VDC) with Drawer Compulsion
<b>Data Buffer – Receive Buffer:</b>	4 KB RAM Selectable to 64 KB
<b>NV Bit Image Data:</b>	128 KB
<b>User NV Memory:</b>	512 KB
<b>Power Supply:</b>	AC 100 ~ 240 V, 50/60 Hz Adapter Included
<b>Current/Power Usage:</b>	2.0A / 60W
<b>Operating Temperature:</b>	40° ~ 114°F (5° ~ 45°C)
<b>Operating Humidity:</b>	20% ~ 90% RH (Non-Condensing)
<b>Paper Cutting Method:</b>	Auto-Cutter – Selectable Full or Partial Cut
<b>Dimensions:</b>	5-3/4"W x 5-11/16"H x 7-5/8"D
<b>Shipping Weight:</b>	7 lbs.
<b>Safety and EMI:</b>	FCC, RoHS

